



# SAFETY DATA SHEET

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Trade name or designation of the mixture	Hydrofuge
Registration number	-
Synonyms	None.
Product code	BDS000625AE
Issue date	22-April-2021
Version number	01

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Cleaners - Precision
Uses advised against	None known.

### 1.3. Details of the supplier of the safety data sheet

Company name	CRC Industries Europe bv
Address	Touwslagerstraat 1 9240 Zele Belgium
Telephone	+32(0)52/45.60.11
Fax	+32(0)52/45.00.34
E-mail	<a href="mailto:hse@crcind.com">hse@crcind.com</a>
Website	<a href="http://www.crcind.com">www.crcind.com</a>

### 1.4. Emergency telephone number

Tel.: +32(0)52/45.60.11 (office hours)

<b>General in EU</b>	112 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
<b>Austria National Poisons Information Centre</b>	+431 406 4343 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
<b>Belgium National Poisons Control Center</b>	070 245 245 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
<b>Bulgaria National Toxicological Information Centre</b>	+359 2 9154233 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
<b>Czech Republic National Poisons Information Centre</b>	+420 224 919 293, or +420 224 915 402 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)
<b>Denmark National Poisons Control Center</b>	+45 82 12 12 12 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
<b>Estonia National Poisons Information Centre</b>	16662 or abroad: (+372) 626 9390 (Monday 9:00AM to Saturday 9:00AM (closed on Sundays and on national holidays). SDS/Product information may not be available for the Emergency Service.)
<b>Finland National Poison Information Center</b>	(09) 471 977 (direct) or (09) 4711 (exchange) (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
<b>France National Poisons Control Center</b>	ORFILA number (INRS): + 33 (0) 1 45 42 59 59 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
<b>Hungary National Emergency Phone Number</b>	36 80 20 11 99 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
<b>Lithuania Neatidėliotina informacija apsinuodijus</b>	+370 5 236 20 52 or +37068753378 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)
<b>Malta Accident and Emergency Department</b>	2545 4030 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)

<b>Netherlands National Poisons Information Center (NVIC)</b>	030-274 88 88 (Only for the purpose of informing medical personnel in cases of acute intoxications)
<b>Norway Norwegian Poison Information Center</b>	22 59 13 00 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
<b>Romania Biroul RSI si Informare Toxicologica</b>	021.318.36.06 (Available 8:00AM-3:00PM. SDS/Product information may not be available for the Emergency Service.)
<b>Slovakia National Toxicological Information Centre</b>	+421 2 5477 4166 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
<b>Sweden National Poison Information Center</b>	112 - and ask for Poison Information (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

#### Classification according to Regulation (EC) No 1272/2008 as amended

##### Physical hazards

Aerosols	Category 1	H222 - Extremely flammable aerosol. H229 - Pressurized container: May burst if heated.
----------	------------	---

##### Health hazards

Skin corrosion/irritation	Category 2	H315 - Causes skin irritation.
Serious eye damage/eye irritation	Category 2	H319 - Causes serious eye irritation.
Specific target organ toxicity - single exposure	Category 3 narcotic effects	H336 - May cause drowsiness or dizziness.

##### Hazard summary

Aerosol CONTENTS UNDER PRESSURE.  
Pressurised container may explode when exposed to heat or flame. May cause drowsiness or dizziness. Causes serious eye irritation. Causes skin irritation. Occupational exposure to the substance or mixture may cause adverse health effects.

### 2.2. Label elements

#### Label according to Regulation (EC) No. 1272/2008 as amended

**Contains:** Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

##### Hazard pictograms



##### Signal word

Danger

##### Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurized container: May burst if heated.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

##### Precautionary statements

###### Prevention

P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P261	Avoid breathing mist/vapours.
P271	Use only outdoors or in a well-ventilated area.

###### Response

Not assigned.

###### Storage

P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
-------------	--

###### Disposal

**Supplemental label information** EUH208 - Contains Calcium petroleum sulfonate, Benzenesulfonic acid, C10-16-alkyl derivatives, calcium salts, Benzenesulfonic acid, di-C10-18-alkyl derivatives, calcium salts. May produce an allergic reaction.

**2.3. Other hazards** This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII. The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	75 - 100	EC919-857-5 -	01-2119463258-33	-	
<b>Classification:</b> Flam. Liq. 3;H226, STOT SE 3;H336, Asp. Tox. 1;H304					
3-butoxypropan-2-ol; propylene glycol monobutyl ether	5 - 10	5131-66-8 225-878-4	01-2119475527-28	603-052-00-8	
<b>Classification:</b> Skin Irrit. 2;H315, Eye Irrit. 2;H319					
Carbon dioxide	1 - 5	124-38-9 204-696-9	Exempt	-	#
<b>Classification:</b> Press. Gas;H280					
Benzenesulfonic acid, C10-16-alkyl derivatives, calcium salts	0 - 1	68584-23-6 271-529-4	01-2119492627-25	-	
<b>Classification:</b> Skin Sens. 1B;H317					
Benzenesulfonic acid, di-C10-18-alkyl derivatives, calcium salts	0 - 1	93820-57-6 298-637-4	-	-	
<b>Classification:</b> Skin Sens. 1;H317					
Calcium petroleum sulfonate	0 - 1	61789-86-4 263-093-9	01-2119488992-18	-	
<b>Classification:</b> Skin Sens. 1;H317					

#### List of abbreviations and symbols that may be used above

#: This substance has been assigned Union workplace exposure limit(s).

M: M-factor

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

**Composition comments** The full text for all H-statements is displayed in section 16.

## SECTION 4: First aid measures

**General information** Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

### 4.1. Description of first aid measures

**Inhalation** Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison centre or doctor/physician if you feel unwell.

**Skin contact** Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

**Eye contact** Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

**Ingestion** In the unlikely event of swallowing contact a physician or poison control centre. Rinse mouth.

**4.2. Most important symptoms and effects, both acute and delayed** May cause drowsiness or dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.

**4.3. Indication of any immediate medical attention and special treatment needed** Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

## SECTION 5: Firefighting measures

**General fire hazards** Extremely flammable aerosol.

### 5.1. Extinguishing media

**Suitable extinguishing media** Foam. Dry chemical powder. Carbon dioxide (CO2).

<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.
<b>5.2. Special hazards arising from the substance or mixture</b>	Contents under pressure. Pressurised container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
<b>5.3. Advice for firefighters</b>	
<b>Special protective equipment for firefighters</b>	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
<b>Special fire fighting procedures</b>	Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapour pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
<b>Specific methods</b>	Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion do not breathe fumes.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

<b>For non-emergency personnel</b>	Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapours. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not touch or walk through spilled material.
<b>For emergency responders</b>	Keep unnecessary personnel away. Avoid breathing mist/vapours. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. Use personal protection recommended in Section 8 of the SDS.

**6.2. Environmental precautions** Avoid discharge into drains, water courses or onto the ground.

**6.3. Methods and material for containment and cleaning up** Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. The product is immiscible with water and will spread on the water surface. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

**6.4. Reference to other sections** For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

## SECTION 7: Handling and storage

**7.1. Precautions for safe handling** Pressurised container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing mist/vapours. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

**7.2. Conditions for safe storage, including any incompatibilities** Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS). Storage class (TRGS 510): 2B (Aerosol dispensers and lighters)

**7.3. Specific end use(s)** Not available.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

##### Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	Ceiling	18000 mg/m <sup>3</sup>
		10000 ppm
	MAK	9000 mg/m <sup>3</sup> 5000 ppm

##### Belgium. Exposure Limit Values

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	STEL	54784 mg/m <sup>3</sup>
		30000 ppm

**Belgium. Exposure Limit Values**

Components	Type	Value
	TWA	9131 mg/m <sup>3</sup> 5000 ppm

**Bulgaria. OELs. Regulation No 13 on protection of workers against risks of exposure to chemical agents at work**

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m <sup>3</sup> 5000 ppm

**Croatia. Dangerous Substance Exposure Limit Values in the Workplace (ELVs), Annexes 1 and 2, Narodne Novine, 13/09**

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	MAC	9000 mg/m <sup>3</sup> 5000 ppm

**Czech Republic. OELs. Government Decree 361**

Components	Type	Value
3-butoxypropan-2-ol; propylene glycol monobutyl ether (CAS 5131-66-8)	Ceiling	550 mg/m <sup>3</sup>
	TWA	270 mg/m <sup>3</sup>
Carbon dioxide (CAS 124-38-9)	Ceiling	45000 mg/m <sup>3</sup>
	TWA	9000 mg/m <sup>3</sup>

**Denmark**

Components	Type	Value
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	TWA	25 ppm

**Denmark. Exposure Limit Values**

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TLV	9000 mg/m <sup>3</sup> 5000 ppm

**Estonia. OELs. Occupational Exposure Limits of Hazardous Substances (Regulation No. 105/2001, Annex), as amended**

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m <sup>3</sup> 5000 ppm

**Finland**

Components	Type	Value
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	TWA	500 mg/m <sup>3</sup>

**Finland. Workplace Exposure Limits**

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9100 mg/m <sup>3</sup> 5000 ppm

**France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984**

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	VME	9000 mg/m <sup>3</sup> 5000 ppm
<b>Regulatory status:</b>	Regulatory indicative (VRI)	
<b>Regulatory status:</b>	Regulatory indicative (VRI)	

**Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG)**

<b>Components</b>	<b>Type</b>	<b>Value</b>	<b>Form</b>
Calcium petroleum sulfonate (CAS 61789-86-4)	TWA	5 mg/m <sup>3</sup>	Respirable fraction.
Carbon dioxide (CAS 124-38-9)	TWA	9100 mg/m <sup>3</sup> 5000 ppm	

**Germany - TRGS 900**

<b>Components</b>	<b>Type</b>	<b>Value</b>
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	TWA	300 mg/m <sup>3</sup>

**Germany. TRGS 900, Limit Values in the Ambient Air at the Workplace**

<b>Components</b>	<b>Type</b>	<b>Value</b>	<b>Form</b>
Calcium petroleum sulfonate (CAS 61789-86-4)	AGW	5 mg/m <sup>3</sup>	Respirable fraction.
Carbon dioxide (CAS 124-38-9)	AGW	9100 mg/m <sup>3</sup> 5000 ppm	

**Greece. OELs (Decree No. 90/1999, as amended)**

<b>Components</b>	<b>Type</b>	<b>Value</b>
Carbon dioxide (CAS 124-38-9)	STEL	54000 mg/m <sup>3</sup> 5000 ppm
	TWA	9000 mg/m <sup>3</sup> 5000 ppm

**Hungary. OELs. Joint Decree on Chemical Safety of Workplaces**

<b>Components</b>	<b>Type</b>	<b>Value</b>
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m <sup>3</sup>
Petrolatum (CAS 8009-03-8)	TWA	5 mg/m <sup>3</sup>

**Iceland. OELs. Regulation 154/1999 on occupational exposure limits**

<b>Components</b>	<b>Type</b>	<b>Value</b>
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m <sup>3</sup> 5000 ppm

**Ireland. Occupational Exposure Limits**

<b>Components</b>	<b>Type</b>	<b>Value</b>
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m <sup>3</sup> 5000 ppm

**Italy. Occupational Exposure Limits**

<b>Components</b>	<b>Type</b>	<b>Value</b>
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m <sup>3</sup> 5000 ppm

**Latvia. OELs. Occupational exposure limit values of chemical substances in work environment**

<b>Components</b>	<b>Type</b>	<b>Value</b>
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m <sup>3</sup> 5000 ppm

**Lithuania. OELs. Limit Values for Chemical Substances, General Requirements**

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3
		5000 ppm

**Luxembourg. Binding Occupational exposure limit values (Annex I), Memorial A**

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3
		5000 ppm

**Malta. OELs. Occupational Exposure Limit Values (L.N. 227. of Occupational Health and Safety Authority Act (CAP. 424), Schedules I and V)**

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3
		5000 ppm

**Netherlands. OELs (binding)**

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3

**Norway**

Components	Type	Value
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	TWA	275 mg/m3

**Norway. Administrative Norms for Contaminants in the Workplace**

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TLV	9000 mg/m3
		5000 ppm

**Poland. Ordinance of the Minister of Labour and Social Policy on 6 June 2014 on the maximum permissible concentrations and intensities of harmful health factors in the work environment, Journal of Laws 2014, item 817**

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	STEL	27000 mg/m3
	TWA	9000 mg/m3

**Portugal. OELs. Decree-Law n. 290/2001 (Journal of the Republic - 1 Series A, n.266)**

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3
		5000 ppm

**Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796)**

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	STEL	30000 ppm
	TWA	5000 ppm

**Romania. OELs. Protection of workers from exposure to chemical agents at the workplace**

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3
		5000 ppm

**Slovakia. OELs. Regulation No. 300/2007 concerning protection of health in work with chemical agents**

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3

**Slovakia. OELs. Regulation No. 300/2007 concerning protection of health in work with chemical agents**

Components	Type	Value
		5000 ppm

**Slovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while working (Official Gazette of the Republic of Slovenia)**

Components	Type	Value	Form
Calcium petroleum sulfonate (CAS 61789-86-4)	TWA	5 mg/m <sup>3</sup>	Respirable fraction.
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m <sup>3</sup>	
		5000 ppm	

**Spain. Occupational Exposure Limits**

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9150 mg/m <sup>3</sup>
		5000 ppm

**Sweden**

Components	Type	Value
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	STEL (STV)	600 mg/m <sup>3</sup>
	TWA	300 mg/m <sup>3</sup>

**Sweden. OELs. Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2015:7)**

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	STEL	18000 mg/m <sup>3</sup>
		10000 ppm
	TWA	9000 mg/m <sup>3</sup>
		5000 ppm

**Switzerland**

Components	Type	Value
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	STEL	6000 mg/m <sup>3</sup>
	TWA	300 mg/m <sup>3</sup>

**Switzerland. SUVA Grenzwerte am Arbeitsplatz**

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m <sup>3</sup>
		5000 ppm

**UK. EH40 Workplace Exposure Limits (WELs)**

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	STEL	27400 mg/m <sup>3</sup>
		15000 ppm
	TWA	9150 mg/m <sup>3</sup>
		5000 ppm

**EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU**

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m <sup>3</sup>
		5000 ppm

**Biological limit values** No biological exposure limits noted for the ingredient(s).

**Recommended monitoring procedures** Follow standard monitoring procedures.



## Derived no effect levels (DNELs)

### General Population

Components	Value	Assessment factor	Notes
3-butoxypropan-2-ol; propylene glycol monobutyl ether (CAS 5131-66-8)			
Long-term, Systemic, Dermal	22 mg/kg bw/day	28	Repeated dose toxicity
Long-term, Systemic, Inhalation	43 mg/m <sup>3</sup>	7	Repeated dose toxicity
Long-term, Systemic, Oral	12,5 mg/kg bw/day	28	Repeated dose toxicity
Benzenesulfonic acid, C10-16-alkyl derivatives, calcium salts (CAS 68584-23-6)			
Long-term, Local, Dermal	0,513 mg/cm <sup>2</sup>	10	Skin Sensitisation
Long-term, Systemic, Inhalation	2,9 mg/m <sup>3</sup>	150	Repeated dose toxicity
Calcium petroleum sulfonate (CAS 61789-86-4)			
Long-term, Local, Dermal	0,513 mg/cm <sup>2</sup>	10	Skin Sensitisation
Long-term, Systemic, Inhalation	2,9 mg/m <sup>3</sup>	150	Repeated dose toxicity
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics (CAS EC919-857-5)			
Long-term, Systemic, Dermal	300 mg/kg		
Long-term, Systemic, Inhalation	900 mg/m <sup>3</sup>		
Long-term, Systemic, Oral	300 mg/kg		

### Workers

Components	Value	Assessment factor	Notes
3-butoxypropan-2-ol; propylene glycol monobutyl ether (CAS 5131-66-8)			
Long-term, Systemic, Dermal	52 mg/kg bw/day	16,8	Repeated dose toxicity
Long-term, Systemic, Inhalation	147 mg/m <sup>3</sup>	4,2	Repeated dose toxicity
Benzenesulfonic acid, C10-16-alkyl derivatives, calcium salts (CAS 68584-23-6)			
Long-term, Local, Dermal	1,03 mg/cm <sup>2</sup>	5	Skin Sensitisation
Long-term, Systemic, Inhalation	11,75 mg/m <sup>3</sup>	75	Repeated dose toxicity
Calcium petroleum sulfonate (CAS 61789-86-4)			
Long-term, Local, Dermal	1,03 mg/cm <sup>2</sup>	5	Skin Sensitisation
Long-term, Systemic, Inhalation	11,75 mg/m <sup>3</sup>	75	Repeated dose toxicity
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics (CAS EC919-857-5)			
Long-term, Systemic, Dermal	300 mg/kg		
Short-term, Systemic, Inhalation	1500 mg/m <sup>3</sup>		
Petrolatum (CAS 8009-03-8)			
Long-term, Systemic, Dermal	5,8 mg/kg		
Long-term, Systemic, Inhalation	2,7 mg/m <sup>3</sup>		

## Predicted no effect concentrations (PNECs)

Components	Value	Assessment factor	Notes
3-butoxypropan-2-ol; propylene glycol monobutyl ether (CAS 5131-66-8)			
Freshwater	0,525 mg/l	1000	
Sediment (freshwater)	2,36 mg/kg		
Soil	0,16 mg/kg		

## 8.2. Exposure controls

### Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

### Individual protection measures, such as personal protective equipment

#### General information

Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.

#### Eye/face protection

Wear safety glasses with side shields (or goggles). Use eye protection conforming to EN 166.

#### Skin protection

##### - Hand protection

When handling the product wear chemical-resistant gloves (standard EN 374). The breakthrough time of the glove should be longer than the total duration of product use. If work lasts longer than the breakthrough time, gloves should be changed part-way through. Suitable gloves can be recommended by the glove supplier. Full contact: Glove material: nitrile. Use gloves with breakthrough time of 480 minutes. Minimum glove thickness 0.38 mm.

##### - Other

Wear appropriate chemical resistant clothing.

#### Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment. Chemical respirator with organic vapour cartridge and full facepiece. (Filter type A)

#### Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

<b>Hygiene measures</b>	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.
<b>Environmental exposure controls</b>	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Fume scrubbers, filters or engineering modifications to the process equipment may be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>Physical state</b>	Liquid.
<b>Form</b>	Aerosol
<b>Colour</b>	Amber.
<b>Odour</b>	Characteristic odor.
<b>Melting point/freezing point</b>	-85 °C (-121 °F) estimated
<b>Boiling point or initial boiling point and boiling range</b>	Not available.
<b>Flammability (solid, gas)</b>	Not available.
<b>Upper/lower flammability or explosive limits</b>	
<b>Flammability limit - lower (%)</b>	Not available.
<b>Flammability limit - upper (%)</b>	Not available.
<b>Flash point</b>	41,0 °C (105,8 °F) Closed cup
<b>Auto-ignition temperature</b>	> 200 °C (> 392 °F)
<b>Decomposition temperature</b>	Not available.
<b>pH</b>	Not applicable.
<b>Solubility(ies)</b>	
<b>Solubility (water)</b>	Insoluble in water
<b>Vapour pressure</b>	2591,9 hPa estimated
<b>Vapour density</b>	Not available.
<b>Relative density</b>	0,78 g/cm <sup>3</sup>
<b>Relative density temperature</b>	20 °C (68 °F)
<b>Particle characteristics</b>	Not available.
<b>9.2 Other safety characteristics</b>	
<b>Explosive properties</b>	Not explosive.
<b>Oxidising properties</b>	Not oxidising.
<b>VOC</b>	705 g/l

## SECTION 10: Stability and reactivity

<b>10.1. Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>10.2. Chemical stability</b>	Material is stable under normal conditions.
<b>10.3. Possibility of hazardous reactions</b>	No dangerous reaction known under conditions of normal use.
<b>10.4. Conditions to avoid</b>	Avoid high temperatures.
<b>10.5. Incompatible materials</b>	Strong oxidising agents.
<b>10.6. Hazardous decomposition products</b>	Carbon oxides.

## SECTION 11: Toxicological information

<b>General information</b>	Occupational exposure to the substance or mixture may cause adverse effects.
<b>Information on likely routes of exposure</b>	
<b>Inhalation</b>	May cause drowsiness or dizziness. Headache. Nausea, vomiting. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Prolonged inhalation may be harmful.
<b>Skin contact</b>	Causes skin irritation. May cause an allergic skin reaction.
<b>Eye contact</b>	Causes serious eye irritation.
<b>Ingestion</b>	May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of occupational exposure.

**Symptoms** May cause drowsiness or dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.

### 11.1. Information on toxicological effects

**Acute toxicity** Based on available data, the classification criteria are not met. Classification based on calculation method.

Product	Species	Test Results
---------	---------	--------------

Hydrofuge

**Acute**

**Dermal**

LD50	Rat	12870 mg/kg
------	-----	-------------

Components	Species	Test Results
------------	---------	--------------

3-butoxypropan-2-ol; propylene glycol monobutyl ether (CAS 5131-66-8)

**Acute**

**Dermal**

LD50	Rabbit	> 2000 mg/kg
------	--------	--------------

**Inhalation**

LC0	Rat	> 3,5 mg/l, 4 h
-----	-----	-----------------

**Oral**

LD50	Rat	3300 mg/kg
------	-----	------------

Benzenesulfonic acid, C10-16-alkyl derivatives, calcium salts (CAS 68584-23-6)

**Acute**

**Oral**

LD50	Rat	> 20000 mg/kg
------	-----	---------------

Calcium petroleum sulfonate (CAS 61789-86-4)

**Acute**

**Dermal**

LD50	Rat	> 4000 mg/kg
------	-----	--------------

**Oral**

LD50	Rat	> 16000 mg/kg
------	-----	---------------

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

**Acute**

**Dermal**

*Liquid*

LD50	Rabbit	> 5000 mg/kg
------	--------	--------------

**Oral**

*Liquid*

LD50	Rat	> 5000 mg/kg
------	-----	--------------

**Skin corrosion/irritation** Causes skin irritation.

**Serious eye damage/eye irritation** Causes serious eye irritation.

**Respiratory sensitisation** Based on available data, the classification criteria are not met.

**Skin sensitisation** Based on available data, the classification criteria are not met.

**Germ cell mutagenicity** Based on available data, the classification criteria are not met.

**Carcinogenicity** Based on available data, the classification criteria are not met.

**Hungary. 26/2000 EüM Ordinance on protection against and preventing risk relating to exposure to carcinogens at work (as amended)**

Not listed.

**Reproductive toxicity** Based on available data, the classification criteria are not met.

**Specific target organ toxicity - single exposure** May cause drowsiness or dizziness.

**Specific target organ toxicity - repeated exposure** Based on available data, the classification criteria are not met.

**Aspiration hazard** Not likely, due to the form of the product.

**Mixture versus substance information** Not available.

## 11.2. Information on other hazards

**Endocrine disrupting properties** The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

**Other information** May cause allergic respiratory and skin reactions.

## SECTION 12: Ecological information

**12.1. Toxicity** The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components	Species	Test Results
3-butoxypropan-2-ol; propylene glycol monobutyl ether (CAS 5131-66-8)		
<b>Aquatic</b>		
<i>Acute</i>		
Algae	EC50	Algae > 1000 mg/l, 96 h
Fish	LC50	Fish 560 - 1000 mg/l, 96 h
Calcium petroleum sulfonate (CAS 61789-86-4)		
<b>Aquatic</b>		
<i>Acute</i>		
Fish	LC50	Fish > 10000 mg/kg
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics		
<i>Acute</i>		
Other	LC50	Pseudokirchnerella subcapitata > 1000 mg/l, 72 h
<b>Aquatic</b>		
<i>Acute</i>		
Fish	LC50	Oncorhynchus mykiss > 1000 mg/l

**12.2. Persistence and degradability** No data is available on the degradability of any ingredients in the mixture.

**12.3. Bioaccumulative potential** No data available.

**Partition coefficient n-octanol/water (log Kow)** Not available.

**Bioconcentration factor (BCF)** Not available.

**12.4. Mobility in soil** No data available.

**12.5. Results of PBT and vPvB assessment** This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII.

**12.6. Endocrine disrupting properties** None known

**12.7. Other adverse effects** The product contains volatile organic compounds which have a photochemical ozone creation potential.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

**Residual waste** Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

**Contaminated packaging** Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

**EU waste code** The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.

**Disposal methods/information** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.

**Special precautions** Dispose in accordance with all applicable regulations.

## SECTION 14: Transport information

### ADR

**14.1. UN number** UN1950

14.2. UN proper shipping name AEROSOLS

14.3. Transport hazard class(es)

Class 2.1

Subsidiary risk -

Hazard No. (ADR) Not available.

Tunnel restriction code (D)

ADR/RID - Classification code: 5F

14.4. Packing group Not applicable

14.5. Environmental hazards No

14.6. Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

#### IATA

14.1. UN number UN1950

14.2. UN proper shipping name AEROSOLS

14.3. Transport hazard class(es)

Class 2.1

Subsidiary risk -

14.4. Packing group Not applicable

14.5. Environmental hazards No

14.6. Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

#### IMDG

14.1. UN number UN1950

14.2. UN proper shipping name AEROSOLS

14.3. Transport hazard class(es)

Class 2.1

Subsidiary risk -

14.4. Packing group Not applicable

14.5. Environmental hazards

Marine pollutant No

EmS F-D, S-U

14.6. Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

14.7. Maritime transport in bulk according to IMO instruments Not established.

ADR; IATA; IMDG



## SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended

Not listed.

Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended

Not listed.

- Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended**  
Not listed.
- Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended**  
Not listed.
- Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended**  
Carbon dioxide (CAS 124-38-9)
- Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA**  
Not listed.

#### Authorisations

- Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended**  
Not listed.

#### Restrictions on use

- Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended**  
Not listed.
- Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.**  
Not listed.

#### Other EU regulations

- Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended**  
Not listed.

#### Other regulations

The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006, as amended.

#### National regulations

This safety data sheet conforms to the following laws, regulations and standards:  
This safety data sheet conforms to the following laws, regulations and standards:  
Act on the management of packaging and packaging waste of June 13, 2013  
Regulation of the Minister of Health of June 11, 2012 on the categories of dangerous substances and dangerous preparations whose packaging should be fitted with child-resistant closures and a tactile warning of danger  
REGULATION OF THE MINISTER OF HEALTH of February 2, 2011 on tests and measurements of factors harmful to health in working environments  
Regulation of Ministry of Labor and Social Policy of June 6, 2014. On the matter of maximum permissible concentrations and intensities of harmful factors in the work environment (Journal of Laws 2014, item. 817)  
Chemical Safety at Workplace Ordinance Joint Decree No. 25/2000 (Annex 2): Permissible limit values of biological exposure (effect) indices Decree No. 25/2000. (IX. 30.) EüM-SzCsM of the Minister of Health and the Minister of Social and Family Affairs on chemical safety at work  
Act No. 93 of 1993 on Labour Safety (1993. évi XCIII.), as amended  
Government Decree No. 220 of 2004 (VII. 21.) providing rules on the protection of surface waters quality  
Government Decree No. 98/2001 (VI. 15.), on the conditions of the activities related to hazardous waste, and Ministry of Environmental Affairs Decree No. 16/2001 (VII. 18.), on the register of waste  
s Public Act No. XXV of 2000 on Chemical Safety, and Application Decree No. 44/2000. (XII.27.) EüM [of the Ministry of Health]  
Follow national regulation for work with chemical agents in accordance with Directive 98/24/EC, as amended.

#### 15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out.

### SECTION 16: Other information

#### List of abbreviations

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways.  
ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.  
ADR: European Agreement Concerning the International Carriage of Dangerous Goods by Road.  
AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert – Germany).  
ATE: Acute Toxicity Estimate according to REGULATION (EC) No 1272/2008 (CLP).  
CAS: Chemical Abstract Service.  
Ceiling: Short Term Exposure Limit Ceiling value.  
CEN: European Committee for Standardization.  
CLP: Classification, Labeling and Packaging REGULATION (EC) No 1272/2008 on classification, labeling and packaging of substances and mixtures.  
GWP: Global Warming Potential.  
IATA: International Air Transport Association.  
IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk.

IMDG: International Maritime Dangerous Goods.  
MAC: Maximum Allowed Concentration.  
MAK: Threshold limit values Germany (Maximale Arbeitsplatzkonzentration - DFG).  
MARPOL: International Convention for the Prevention of Pollution from Ships.  
PBT: Persistent, bioaccumulative and toxic.  
REACH: Registration, Evaluation and Authorization of Chemicals (REGULATION (EC) No 1907/2006 concerning Registration, Evaluation Authorization and Restriction of Chemicals).  
RID: Regulations concerning the international carriage of dangerous goods by rail (Règlement International concernant le transport de marchandises dangereuses par chemin de fer).  
RID: Regulations concerning the International Carriage of Dangerous Goods by Rail.  
STEL: Short term exposure limit.  
TLV: Threshold Limit Value.  
TWA: Time Weighted Average.  
VLE: Exposure Limit Value.  
VME: Exposure Average Value.  
VOC: Volatile organic compounds.  
vPvB: Very persistent and very bioaccumulative.  
STEL: Short-term Exposure Limit.

#### References

Not available.

#### Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

#### Full text of any H-statements not written out in full under Sections 2 to 15

H226 Flammable liquid and vapour.  
H280 Contains gas under pressure; may explode if heated.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.

#### Revision information

None.

#### Training information

Follow training instructions when handling this material.

#### Disclaimer

CRC Industries Europe bvba cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.